



ELAMS

Expandable Light Air Mobile Shelter



ELAMS



P/N	NSN	COLOR	GSA	DLA
58200-022 (91.38\"H)	8145-01-494-5922	GREEN	●	●
58200-020 (91.38\"H)	8145-01-468-5926	TAN	●	●
58200-052 (96.25\"H)		GREEN	●	●
58200-053 (96.25\"H)		TAN	●	●
DIMENSIONS				
STOWED EXTERIOR	96\"W X 178\"L X 91.38\" or 96.25\"H			
STOWED INTERIOR	92.6\"W X 174.3\"L X 81\" or 87\"H			
DEPLOYED EXTERIOR	266\"W X 178\"L X 91.38\" or 96.25\"H			
DEPLOYED INTERIOR	263\"W X 174.3\"L X 81\" or 87\"H			
TARE WEIGHT	PAYLOAD CAPACITY	MAXIMUM WEIGHT		
3,840 lbs. 91.4\"H	11,160 lbs.	15,000 lbs.		
4,080 lbs. 96.25\"H	10,920 lbs.	15,000 lbs.		
POWER	120-208VAC/3PH/60A/60Hz			
ECU	36K BTU-Cool/18K BTU-Heat/Slide In/Out			
FLOORING	Aluminum Tread Plate			
CANVAS	P/N 60386-002/001/005/006			
SAFETY KIT	60389-002			
STRUT ASSEMBLY	58200-245/243			



ELAMS deployed in expanded mode.

FEATURES

- Designed to function mounted on a vehicle or on the ground
- Fits on most military and commercial trucks as well as flatracks
- 2-Way Forkliftable using standard 10,000 lb. forklift with 72\" tines
- Can be easily erected in minutes by two people and be ready for short- or long-term missions
- See Shelter Accessories on page 3.5.1

APPLICATIONS

- Command Posts
- Sleeping Quarters
- Field Kitchens
- Ablution Units
- Medical Facilities
- Shower Complexes
- Workshops
- Briefing Rooms



ELAMS deployed and configured with an ablation unit

For more information or for a single part number for a customized shelter, call 800-355-2015

AVITEC Sp. z o. o.
ul. Wincentego Pola 35A
58-500 Jelenia Góra

NIP: 6112769246
REGON: 365522922
KRS: 0000634315

Contact:
+48 75 64-13-311
+48 75 64-13-319
office@avitec.pl